

CHRISTOPHER J. GARNER
DIRECTOR

211 EAST OCEAN BLVD., SUITE 500 · LONG BEACH, CA 90802 (562) 570-3900 · FAX (562) 570-3922

OIL OPERATIONS . OIL PRODUCTION / SUBSIDENCE

September 9, 2008

HONORABLE MAYOR AND CITY COUNCIL City of Long Beach California

RECOMMENDATION:

Receive and file the attached report, "Elevation Changes in the City of Long Beach, November 2007 through April 2008." (Citywide)

DISCUSSION

The City of Long Beach (City), through the Long Beach Gas and Oil Department (LBGO), supervises oil production and subsidence control operations in the Wilmington Oil Field. LBGO conducts elevation surveys every six months to monitor elevation changes in the oil fields and adjacent City areas. This report focuses on elevation changes that have occurred from November 2007 through April 2008. The LBGO survey includes the following areas: Civic Center, Central City, Alamitos Bay, Naples, Harbor District, and an offshore area encompassing the four offshore oil islands.

The results of the six-month survey show that elevations were stable in the Civic Center, Central City, Alamitos Bay, Naples, and offshore areas. Harbor District elevations were stable except in one small area where an elevation loss of up to 0.070 feet (0.840 inches) was observed overlying parts of Piers A and S, adjacent to the Cerritos Channel. There is no reason for concern as this area had minor elevation changes due to waterflood adjustments corresponding to oil field development programs. LBGO is mitigating the elevation change in the area by increasing and realigning water injection.

The LBGO survey uses a series of bench marks to determine elevation changes. Studies by the Department's engineers and geologists show that the bench marks may rise and fall in such a manner as to make a survey either optimistic (slightly up in elevation) or pessimistic (slightly down in elevation). These changes in elevations may be associated with tidal cycles, temperature changes, and/or deep earth tectonic

HONORABLE MAYOR AND CITY COUNCIL September 9, 2008 Page 2

changes or repressuring operations. Surface elevations in a rebounded area can be expected to fluctuate under changing water flood conditions.

Principal Deputy City Attorney Charles Parkin reviewed this item on August 19, 2008.

TIMING CONSIDERATIONS

City Council action on this matter is not time critical.

FISCAL IMPACT

There is no fiscal impact associated with this action.

SUGGESTED ACTION:

Approve recommendation.

Respectfully submitted,

CHRISTOPHER J. GARNER

DIRECTOR OF LONG BEACH GAS AND OIL

CJG:jdj

APPROVED:

Attachment

PATRICK H. WEST CITY MANAGER

ELEVATION CHANGES IN THE CITY OF LONG BEACH

NOVEMBER 2007 THROUGH APRIL 2008

PREPARED

FOR

LONG BEACH CITY COUNCIL

BY THE

LONG BEACH GAS AND OIL DEPARTMENT

CONTENTS

| | | _ |
|------|--|-------------|
| 1. | SUBSIDENCE AND REBOUND SURVEY ANALYSIS | <u>Page</u> |
| | Elevation Change – November 2007 through April 2008 | 3 |
| | Elevation Change – May 2007 through April 2008 | 4 |
| | Use of Global Positioning System (GPS) | 4 |
| II. | APPENDIX | |
| | Brief History of Long Beach Subsidence | 5 |
| | Survey Accuracy | 6 |
| | Elevation Change Map Construction | 7 |
| | Bench Mark Location Map | 7 |
| | Bench Mark and Net Injection Graphs, Harbor District | 7 |
| | Bench Mark and Net Injection Graphs, Ocean Boulevard and Offshore Drilling Islands | 8 |
| III. | ELEVATION CHANGE MAPS <u>F</u> | igures |
| | November 2007 through April 2008 | 1 |
| | May 2007 through April 2008 | 2 |
| | BENCH MARK AND NET INJECTION GRAPHS | |
| | Bench Mark Location Map | 3 |
| | Harbor District, Fault Blocks II-V | 4-7 |
| | Ocean Boulevard and Offshore Drilling Islands, Fault Blocks VI through 90S | 8-13 |

ELEVATION SURVEY ANALYSIS

The City of Long Beach semi-annual elevation survey of the Civic Center, Central City, Harbor, Alamitos Bay, Naples, and offshore areas was conducted during May 2008. Changes in elevation that have occurred since the last two surveys, November 2007 and May 2008 are discussed in this report. The results in this report reflect elevation changes both within and beyond the scope of oilfield operations. Some are due to natural geologic factors.

Elevation Change – November 2007 through April 2008 (Figure 1)

Elevations throughout the Civic Center, Alamitos Bay, Naples, and offshore areas were stable during the six-month period.

The Harbor District elevations were stable during the six-month period. Piers A and S experienced a localized elevation decrease of 0.050 to 0.070 feet (0.60 to .84 inches). Elevations at the southern portion of the curtailed Tar II steamflood on Pier A West and adjacent Henry Ford Avenue declined up to 0.050 feet (0.60 inches) during the 6-month period. These minor elevation declines were due to oil production and water injection realignment to the previous focused oil field development program. Water injection volumes have also been increased by Long Beach Gas and Oil (LBGO).

Elevations in the City of Long Beach beyond the boundaries of the Wilmington Oil Field were stable. Minor elevation changes in geologically active areas outside the Wilmington Oil Field indicate that this six-month period was a "down" period semi-regionally.

Elevation Change – May 2007 through April 2008 (Figure 2)

Elevations throughout the Central City, Alamitos Bay, Naples, and offshore areas

remained stable during the 12-month period.

The Harbor District remained stable during the 12-month period except for two minor

changes. A localized elevation gain of up to 0.075 feet (0.90 inches) occurred on Piers D

and E overlying Fault Blocks IV and V. Water injection has been reduced in this area.

An elevation decrease of up to 0.079 feet (0.95 inches) was observed on the northern

portion of Pier S, adjacent to the Cerritos Channel. This decrease was due to the

temporary focused oil field development program. Water injection has been increased to

correct the elevation loss.

Use of Global Positioning System (GPS)

LBGO operates the Long Beach Deformation Network (LBDN) consisting of thirteen (13)

permanent, reference GPS base stations. This report is based solely upon computer

processed LBDN bench mark elevation data generated from GPS satellites.

elevation measurements have been demonstrated to be reliable and can be more

accurate than the spirit leveling which it replaced. The field data collection time has been

reduced by more than 65 percent and the 800 spirit leveled bench marks have been

reduced to approximately 240 GPS bench marks.

(Reference: Appendix, Survey Accuracy, pg. 7)

4

APPENDIX

Brief History of Long Beach Subsidence

Long Beach and the general vicinity have a history of regional subsidence (losses of elevation) since 1929. Elevation changes were minor amounting to an average of about - 0.036 feet (-0.43 inches) per year until about 1939. Geologic movement such as the Long Beach Earthquake of March 1933 altered this average rate at times. The reason for this slight regional subsidence or slight elevation loss is not fully understood. Contributing causes appear to be groundwater withdrawal from aquifers in the Long Beach area, regional basin sediment compaction, and tectonic effects.

Development of the Wilmington Oil Field began in 1936. Oil operations accelerated subsidence and created a 29-feet deep subsidence bowl centered in the Wilmington-Long Beach Harbor area near Bench Mark 8772 (Figure 6). Development of the Ranger Zone west of Pine Avenue and its extension seaward in 1947 started the first definitive subsidence in the Central Business District that could be attributed to oil production.

Repressuring operations began in the 1950s. By 1965, subsidence stopped throughout the Long Beach portion of the Wilmington Oil Field. Some bench marks have actually recovered over one foot in elevation. This is known as rebound. As an example, from 1960 to 1970, Bench Mark No. 1735 near the corner of Ocean Boulevard and Magnolia Avenue recovered approximately one foot of elevation.

In the 1990s, a large Harbor redevelopment project on Pier A destroyed several bench marks that overlaid the now curtailed steamflood project. Elevation losses in the area were suspected and the destruction of these bench marks made it difficult to monitor any changes. In 1998, after the bench marks were replaced, additional well bore investigations determined that subsurface compaction of the deep shale intervals was occurring above the steam flooded zones due to high temperatures. The Fault Block II Tar Zone Steamflood was terminated in 1999, and cold-water injection was initiated. The forced cooling of the deep formations has remedied the subsidence problem.

The Alamitos Bay and Naples area had losses in elevation prior to development of the adjacent oil operations. These original small losses were most likely due to the regional affects of basin sediment compaction and tectonic movements along the Newport-Inglewood Fault Zone. Later, the coastal strip from the Civic Center eastward to the Alamitos Bay Peninsula lost elevation due to oil and gas production from the West Wilmington Oil Field and possibly the adjacent oil fields. The coastal strip rebounded slightly due to water injection from the offshore Oil Islands that began in 1965.

Survey Accuracy

The May 2002 Elevation Leveling Campaign marked the conversion from spirit, first and second order rod leveling, to GPS measurement of City and Harbor bench mark elevations. Through the GPS contractor, Pinnacle Technologies, Inc., a network of thirteen permanent real-time GPS base stations and a central data collection and processing center were installed within the City of Long Beach. Several existing non-City operated stations were integrated into the new network. The Public Works Department's Bureau of Engineering surveyors utilize mobile GPS equipment linked to the base stations to measure approximately 240 City and Harbor bench marks, down from the previous 800 bench marks.

Through statistical analysis of satellite, base station, and mobile instrument geometries, and a coincident spirit leveling and GPS bench mark elevation survey, City surveyors and Pinnacle estimate the accuracy of GPS elevations to be 6 - 8 millimeters (0.02 feet or 0.24 inches) that is equal to or better than the prior spirit leveling. Areas are considered to be stable where elevation change is less than 0.02 feet (0.24 inches).

Studies by the City's subsidence control engineers, geologists, and consultants show that the bench marks may at times rise and fall somewhat rhythmically city-wide in such a manner as to make an entire survey either optimistic or pessimistic. These elevation changes are random and not well understood. Repressuring operations and the resulting rebound can mask the rise or fall pattern. Surface elevations in a rebounded area can be

expected to fluctuate under changing water flood conditions. Because of these fluctuations, conclusions based upon short-term survey data should be viewed with caution. Short-term survey data are useful for possible early detection and confirmation of subsidence trends or relative elevation changes but should not be accepted without consideration of the above factors. Annual survey data tend to average these fluctuations and depict a more dependable picture of the relative movements of bench marks.

Elevation Change Map Construction (Figure 1 and 2)

All data are presented as contour lines showing the average change in surface elevation during a particular time period. For example, any point along a line reading 0.05 feet (0.60 inches) on an Elevation Change Map gained an elevation of one-twentieth of a foot or six-tenths of an inch during that period. The small hachures along contour lines point towards a loss in elevation.

Bench Mark Location Map (Figure 3)

This map shows the location of bench marks used for the Bench Mark and Net Injection Graphs.

Bench Mark and Net Injection Graphs, Harbor District (Figures 4 - 7)

The bench marks are normalized to mean sea level. Bench marks are plotted each time they are surveyed and are shown on a graph with a history of net injection for that same area and time. The net injection is the amount of water injected into the reservoirs that underlie that particular bench mark minus the gross fluid produced from the reservoirs in barrels per day. The graphs cover 20 years of net injection and bench mark monitoring.

In general, these graphs show a good correlation between the net injection and elevation change. For example, an increase in net injection is usually followed by an increase in elevation. There tends to be a lag time of months and sometimes years between the net injection change and the subsequent elevation change. The elevation plots of bench marks on Figures 4 through 7 in the Harbor District illustrate surface elevation fluctuations

that can be expected to occur under the dynamic reservoir conditions experienced in extremely mature waterflooding operations.

Bench Mark and Net Injection Graphs, Ocean Boulevard and the Offshore Drilling Islands (Figures 8 – 13)

The last 20 years of elevation changes and accompanying net injection histories are shown on Figures 8 through 13 for bench marks located along Ocean Boulevard and on the offshore drilling islands. The elevation changes at Ocean Boulevard near Magnolia Avenue are shown by the graph of Bench Mark 1735 and Bench Mark 1215 on Figure 8. Permanent GPS Station WELL on Figure 12 shows surface elevation changes on the Alamitos Bay Peninsula. Bench Mark 938 monitors elevation on Naples Island.

























