

American

CREMATORY EQUIPMENT CO.

Proudly Serving the Cremation Industry for over 38 Years!



Maximize Profits

With the addition of the "Trilogy" combustion control & monitoring system (shown here) you get the advantage of increased fuel efficiency, advanced monitoring and diagnostic capabilities. The "Trilogy" system allows for immediate and accurate troubleshooting, decreasing and/or eliminating costly down time. American Crematory Equipment Company is proud to be the only manufacture to employ this technology.



A-200-HT

"Hot Hearth" Cremation Equipment

The American A-200-HT Model is our Flagship Cremator. With an average cremation time of 2 hours or less the A-200-HT can easily perform 4-5 cases per day. The primary feature on the A-200-HT is "Throat Air" and "Hearth Air" Control. Throat Air allows the operator the ability to effectively control and eliminate stack emissions. Hearth Air allows the operator full control of the primary chamber over fire air which effectively decreases cremation times. Additionally the combustion process is cycled and monitored by automatic temperature and timer controls which ensure fuel efficiency.

A-200-HT Specifications

Height	8'4" (2.5m)
Length	14'8" (4.47m)
Width	6'3" with Panel (1.82m)
Weight	23,000 Lbs. (10,433 kg)
Installation Clearance Required	8' min. (2.43m)
Fuel	Natural Gas, Propane, Butane, Can be Modified to Accept Diesel Oil
Electrical	220V/60Hz/1 Phase or 3 Phase (Nationally) 240V/50Hz/1 Phase or 3 Phase (Internationally)
Maximum Fuel Rating	1.75MM BTU/HR
Panel	Right, Left or Remote
Warranty	2 year "Best in Class"

Options:

- "Trilogy" Combustion Control & Monitoring System
- "Guardian" PLC, DAS & Touch Screen Control System
- "Aries" Complete Logic Control
- Combustion Blower "Silencer"

Available in a wide range of colors allowing you or our team to design a comforting setting for your customers.

Ask About Our Lease & Finance Options

Sales • Service • Supplies • Repairs

www.AmericanCrematory.com

Corporate Office: (562) 222-2876 • (800) 396-2254 • Fax: (562) 222-2880